



**QMFZ2.E143048
Plastics - Component**

Additional information regarding this certification can be found in UL's iQ Family of Databases (iq.ul.com).

NEW -- for additional information concerning the individual material, click on the material designation.

[Page Bottom](#)

Plastics - Component

[See General Information for Plastics - Component](#)

TARO PLAST SPA
STRADA DIOLO 57/A
43019 SORAGNA, PR ITALY

E143048

Material Dsg	Color	Min. Thk mm	Flame Class	H		R T I		H	D	C	
				W	A	Elec	Mech	V	4		
				I	I	Imp	Str	T	9		T
				I	I			R	5	I	
Acrylonitrile Butadiene Styrene (ABS), "NILSAN", furnished as pellets.											
NILSAN S GP (V)(Z)	ALL	1.5	HB	-	-	60	60	60	-	-	-
NILSAN S V0 L	WT	1.6	V-0	-	-	60	60	60	-	-	-
NILSAN S V0 NB L	ALL	1.6	V-0	-	-	60	60	60	-	-	-
NILSAN S VO	ALL	1.6	V-0	-	-	60	60	60	-	-	-
Acrylonitrile Butadiene Styrene (ABS), "TARODUR", furnished as pellets.											
100	ALL	1.5	HB	-	-	60	60	60	-	-	-
100 X-0	RD	0.97	V-2	-	-	60	60	60	-	-	-
	ALL	1.6	V-0	-	-	60	60	60			
Acrylonitrile Butadiene Styrene/Polycarbonate (ABS/PC), "TAROBLEND", furnished as pellets.											
Taroblend (a)X-0	ALL	1.7	V-0	-	-	50	50	50	-	-	-
Polyamide 6 (PA6), mineral reinforced, flame retardant, "TAROMID", furnished as pellets.											
B 240 MT2 Y2	ALL	0.97-1.5	V-2	-	-	65	65	65	-	-	-
Polyamide 6 (PA6), "TAROMID", furnished as pellets.											
B 240 NG4 Y2	ALL	0.75	V-2	-	-	65	65	65	-	-	-
		1.5	V-2	-	-	65	65	65			
		3.0	V-2	-	-	65	65	65			
B 280 G4 X2	ALL	0.75	V-2	-	-	65	65	65	-	-	-
		3.0	V-0	-	-	65	65	65			
B 280 G5 X-0, B 280 G6 X-0											
	ALL	0.97	V-0	-	-	65	65	65	-	-	-
B 280 G7 X-0	ALL	0.97	V-0	1	0	65	65	65	-	-	3
		3.0	V-0	1	0	65	65	65			
B 280 X-0, B 280 G1 X-0, B 280 G2 X-0, B 280 G3 X-0, B 280 G4 X-0											
	ALL	0.97	V-0	-	-	65	65	65	-	-	-
Polyamide 66 (PA66), mineral reinforced, "TAROMID", furnished as pellets.											
A280 H MG6 DX0	NC	0.75	V-0	-	-	65	65	65	-	-	-
Polyamide 66 (PA66), "TAROMID", furnished as pellets.											
A 280 H G6 DX0 TR-1											
	ALL	0.75	V-0	0	0	130	100	100	-	-	1

		1.5	V-0	0	0	130	115	115			
		3.0	V-0	0	0	130	130	130			
A 280 H G6 X0	NC, BK	0.75	V-0	-	-	140	100	140	-	-	1
	ALL	0.88	V-0	-	-	140	100	140			
		1.5	V-0	-	-	140	115	140			
		3.0	V-0	-	-	140	120	140			
A 280 H G9 DX0 TR-1											
	NC, BK	0.75	V-0	-	-	130	100	100	-	-	1
		1.5	V-0	-	-	130	115	115			
		3.0	V-0	-	-	130	130	130			
Polyamide 66 (PA66), "Taromid", furnished as pellets.											
A 280 HW G(b)	NC	0.75	HB	-	-	65	65	65	-	-	-
Polyamide 66 (PA66), "TAROMID", furnished as pellets.											
A 280 X-0, A 280 G1 X-0, A 280 G2 X-0, A 280 G3 X-0, A 280 G4 X-0, A 280 G5 X-0, A 280 G7 X-0											
	ALL	0.88	V-0	-	-	65	65	65	-	-	-
A260 Y0	ALL	0.55	V-0	-	-	-	-	-	-	-	-
		1.60	V-0	-	-	-	-	-			
		3.0	V-0	-	-	-	-	-			
Polyamide 66 (PA66), "TAROMID".											
A280 G(e) Y0	ALL	0.85	V-0	-	-	65	65	65	-	-	0
		1.5	V-0	-	-	65	65	65			
		3.0	V-0	-	-	65	65	65			
A280 G2 Y0	ALL	0.75	V-0	-	-	65	65	65	-	-	0
		1.5	V-0	-	-	65	65	65			
		3.0	V-0	-	-	65	65	65			
A280 G5 Y0	ALL	0.85	V-0	0	0	65	65	65	-	-	0
		1.5	V-0	0	0	65	65	65			
		3.0	V-0	0	0	65	65	65			
Polybutylene Terephthalate (PBT), glass reinforced, "TAROLOX", furnished as pellets.											
GFR(m)	ALL	0.4	V-0	-	-	75	75	75	-	-	-
		0.75	V-0	-	-	75	75	75			
		1.5	V-0	-	-	75	75	75			
		3.0	V-0	-	-	75	75	75			
Polybutylene Terephthalate (PBT), "TAROLOX", furnished as pellets.											
10 H G6 DX0	NC, BK	0.75	V-0	4	0	130	120	130	-	-	2
		1.5	V-0	2	0	130	130	130			
		3.0	V-0	0	0	130	130	130			
10 H G6 X-0	NC, BK	0.75	V-0	3	0	130	130	140	-	-	2
	ALL	0.97	V-0	3	0	130	130	140			
		1.5	V-0	3	0	130	130	140			
		3.0	V-0	2	0	130	130	140			
10 X-0, 10 G1 X-0, 10 G2 X-0, 10 G3 X-0, 10 G4 X-0, 10 G5 X-0											
	ALL	0.97	V-0	-	-	75	75	75	-	-	-
Polycarbonate (PC), "TAROLON", furnished as pellets.											
2500 W X-0, 2500 W G1 X-0, 2500 W G2 X-0, 2500 W G3 X-0, 2500 W G4 X-0, 2500 W G5 X-0, 2500 W G6 X-0											
	ALL	0.97	V-0	-	-	80	80	80	-	-	-

TAROLON 3002 G3	ALL	1.5	V-2	-	-	80	80	80	-	-	-
		3.0	V-1	-	-	80	80	80			
Polycarbonate (PC), furnished as pellets.											
Tarolon 1520	ALL	1.6	V-2	-	-	80	80	80	-	-	-
Tarolon 2020	ALL	1.6	V-2	-	-	80	80	80	-	-	-
Tarolon 2500 G(d) X1											
	ALL	1.6	V-1	-	-	80	80	80	-	-	-
		3.5	V-0	-	-	80	80	80			
Tarolon 2520	ALL	1.6	V-2	-	-	80	80	80	-	-	-
Tarolon 3020	ALL	1.6	V-2	0	0	80	80	80	-	-	0
		3.0	V-2	0	0	80	80	80			
Polyethylene Terephthalate (PET), glass reinforced, "TAROLOX", furnished as pellets.											
111 G(g) DX02	ALL	0.75	V-2	0	-	75	75	75	-	-	-
		1.5	V-0	0	-	75	75	75			
		3.0	V-0	0	-	75	75	75			
111 G7 DX02	ALL	0.75	V-2	0	0	150	120	130	-	-	3
		1.5	V-0	0	0	150	130	140			
		3.0	V-0	0	0	150	130	140			
Polypropylene (PP), flame retardant, "Haiplen", furnished as pellets.											
HAIPLEN EP(j) Y2	ALL	3.0	V-2	1	0	65	65	65	-	-	0
		1.6	V-2	2	0	65	65	65			
		1.0	V-2	3	0	65	65	65			
Polypropylene (PP), flame retardant, furnished as pellets.											
NILENE E V2 (V) (Z)											
	ALL	0.8	V-2	-	-	65	65	65	-	-	-
NILENE E V2 LBAF (V) (Z)											
	ALL	0.8	V-2	-	-	65	65	65	-	-	-
NILENE E VO LSZH (V) (Z)											
	ALL	1.6	V-0	-	-	65	65	65	-	-	-
Polypropylene (PP), glass reinforced, furnished as pellets.											
NILENE P K 50 VA S (V) (Z)											
	ALL	0.75	HB	-	-	65	65	65	-	-	-
Polypropylene (PP), glass reinforced, flame retardant, furnished as pellets.											
NILENE P K30 VA V0 (V) (Z)											
	ALL	1.6	V-0	-	-	65	65	65	-	-	-
Polypropylene (PP), mineral reinforced, furnished as pellets.											
NILENE E K(h)T (V) (Z)											
	ALL	1.6	HB	-	-	65	65	65	-	-	-
NILENE E K40T (V) (Z)											
	ALL	1.6	HB	-	-	65	65	65	-	-	-
NILENE P K (a) T (V) (Z)											
	ALL	1.6	HB	-	-	65	65	65	-	-	-
NILENE P K(h)T (V) (Z)											
	ALL	1.6	HB	-	-	65	65	65	-	-	-
NILENE P K1T (V) (Z)											
	ALL	1.6	HB	-	-	65	65	65	-	-	-

NILENE P K40T (V) (Z)											
	ALL	1.6	HB	-	-	65	65	65	-	-	-
Polypropylene (PP), resin blend, mineral reinforced, furnished as pellets.											
NILENE E K (a) T (V) (Z)											
	ALL	1.6	HB	-	-	65	65	65	-	-	-
NILENE E K1T (V) (Z)											
	ALL	1.6	HB	-	-	65	65	65	-	-	-
Polypropylene (PP), talc filled, flame retarded, furnished as pellets.											
NILENE E K10T V2 (V) (Z)											
	ALL	1.6	V-2	-	-	65	65	65	-	-	-
NILENE E K20T V0 (V) (Z)											
	ALL	1.6	V-0	-	-	65	65	65	-	-	-
NILENE E K20T V0 W0D (V) (Z)											
	ALL	1.6	V-0	-	-	65	65	65	-	-	-
Polypropylene (PP), furnished as pellets.											
HAIPLN EP50 TC(c) XB											
	ALL	1.5	HB	-	-	65	65	65	-	-	-
HAIPLN H 50 Y0	ALL	1.6	V-0	-	-	65	65	65	-	-	-
HAIPLN H(a)X2	ALL	1.0	-	-	-	65	65	65	-	-	-
		1.5	V-2	-	-	65	65	65			
HAIPLN H30 K6 BA X0(f2)											
	ALL	1.5	V-0	-	-	65	65	65	-	-	-
		3.0	V-0, 5VA	-	-	65	65	65			
HAIPLN H50 T4 X0	ALL	1.5	V-0	-	-	65	65	65	-	-	-
NILENE E (V) (Z)	ALL	1.6	HB	-	-	65	65	65	-	-	-
NILENE P (V) (Z)	ALL	1.6	HB	-	-	65	65	65	-	-	-
NILENE P K (b) VA S (V) (Z)											
	ALL	0.75	HB	-	-	65	65	65	-	-	-
NILENE P K (i) VA S (V) (Z)											
	ALL	1.5	HB	-	-	65	65	65	-	-	-

(a) - Represents a two digit number 10-90 incl.

(b) - Represents one or two digits number from 4 to 10 denoting glass content from 20 to 50 percent

(c) - Represents a one digit number from 2 to 8 denoting mineral content from 10 to 40 percent.

(d) - Represents a one digit number from 4 to 8 denoting glass content from 20 to 40 percent.

(e) - Denotes a number 3, 4, 6 or 7, indicating glass fill percentage of 15%, 20%, 30% or 35%, respectively.

(g) - Represents a one digit number from 4 to 6 denoting glass content from 20 to 30 percent.

(h) - May be replaced by a number 2-39 inclusive, indicating mineral filler content.

(i) - is a number that means glass fiber content from 5 to 49% inclusive

(j) - Represents two or three digit number denoting Melt Flow index between 10 and 200 g/mm.

(m) - Denotes a one digit number from 0 to 6 representing glass filler content from 0 to 30%.

(V) - Represents a generic indication of color [Italian] followed by numeric code [5 numbers] indicating color shade.

(Z) - Represents an optional alphanumeric code [1 or 2 letters plus one number] referring to manufacturing process information.

Marking: Company name and material designation on container, wrapper or finished part.

Last Updated on 2011-03-11

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

[Copyright © 2011 Underwriters Laboratories Inc.®](#)

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2011 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

